

核电缆类

HKJJP



芯数截面 Nominal Cross Section Area	导体结构 Conductor		绝缘厚度 Insulation Thickness /mm	绝缘外径 O.D. of Insulation /mm	护套厚度 Sheath Thickness /mm	标称电缆外径 O.D. of Cable /mm	绝缘电阻最小 /MQ.km Minimum Resistance	
	根 No. of Strands	直径 Diameter/ mm					20℃	90℃
2 × 1	7	0.43	0.7	2.69	1.3	11.3	1170	1.17
2 × 1.5	7	0.52	0.7	2.96	1.3	11.8	1020	1.02
2 × 2.5	7	0.68	0.7	3.44	1.3	12.9	832	0.83
2 × 4	7	0.85	0.7	3.95	1.4	14.0	697	0.70
3 × 1	7	0.43	0.7	2.69	1.3	11.7	1170	1.17
3 × 1.5	7	0.52	0.7	2.96	1.3	12.3	1020	1.02
3 × 2.5	7	0.68	0.7	3.44	1.3	13.4	832	0.83
3 × 4	7	0.85	0.7	3.95	1.4	14.6	697	0.70
4 × 1	7	0.43	0.7	2.69	1.3	12.5	1170	1.17
4 × 1.5	7	0.52	0.7	2.96	1.3	13.2	1020	1.02
4 × 2.5	7	0.68	0.7	3.44	1.4	14.4	832	0.83
4 × 4	7	0.85	0.7	3.95	1.4	15.7	697	0.70
5 × 1	7	0.43	0.7	2.69	1.3	13.3	1170	1.17
5 × 1.5	7	0.52	0.7	2.96	1.4	14.1	1020	1.02
5 × 2.5	7	0.68	0.7	3.44	1.4	15.4	832	0.83
5 × 4	7	0.85	0.7	3.95	1.4	16.9	697	0.70
7 × 1	7	0.43	0.7	2.69	1.4	14.1	1170	1.17
7 × 1.5	7	0.52	0.7	2.96	1.4	15.0	1020	1.02
7 × 2.5	7	0.68	0.7	3.44	1.4	16.5	832	0.83
7 × 4	7	0.85	0.7	3.95	1.5	18.2	697	0.70
8 × 1	7	0.43	0.7	2.69	1.4	15.0	1170	1.17
8 × 1.5	7	0.52	0.7	2.96	1.4	16.0	1020	1.02
8 × 2.5	7	0.68	0.7	3.44	1.5	17.7	832	0.83
8 × 4	7	0.85	0.7	3.95	1.6	19.7	697	0.70
10 × 1	7	0.43	0.7	2.69	1.4	17.0	1170	1.17
10 × 1.5	7	0.52	0.7	2.96	1.5	18.2	1020	1.02
10 × 2.5	7	0.68	0.7	3.44	1.6	20.4	832	0.83
10 × 4	7	0.85	0.7	3.95	1.6	22.6	697	0.70
12 × 1	7	0.43	0.7	2.69	1.5	17.4	1170	1.17
12 × 1.5	7	0.52	0.7	2.96	1.5	18.9	1020	1.02
12 × 2.5	7	0.68	0.7	3.44	1.6	21.0	832	0.83
12 × 4	7	0.85	0.7	3.95	1.6	23.2	697	0.70
14 × 1	7	0.43	0.7	2.69	1.5	18.2	1170	1.17
14 × 1.5	7	0.52	0.7	2.96	1.5	19.7	1020	1.02
14 × 2.5	7	0.68	0.7	3.44	1.6	21.9	832	0.83

核电缆类

HKJJP



芯数截面 Nominal Cross Section Area	导体结构 Conductor		绝缘厚度 Insulation Thickness /mm	绝缘外径 O.D. of Insulation /mm	护套厚度 Sheath Thickness /mm	标称市面外径 O.D. of Cable /mm	绝缘电阻最小值 MQ/km Minimum Resistance	
	根 No. of Strands	直径 Diameter/ mm					20℃	90℃
14 × 4	7	0.85	0.7	3.95	1.7	24.3	697	0.70
16 × 1	7	0.43	0.7	2.69	1.5	19.2	1170	1.17
16 × 1.5	7	0.52	0.7	2.96	1.6	20.6	1020	1.02
16 × 2.5	7	0.68	0.7	3.44	1.6	23.0	832	0.83
16 × 4	7	0.85	0.7	3.95	1.7	25.7	697	0.70
19 × 1	7	0.43	0.7	2.69	1.5	20.1	1170	1.17
19 × 1.5	7	0.52	0.7	2.96	1.6	21.5	1020	1.02
19 × 2.5	7	0.68	0.7	3.44	1.7	24.1	832	0.83
19 × 4	7	0.85	0.7	3.95	1.8	27.0	697	0.70
24 × 1	7	0.43	0.7	2.69	1.6	22.9	1170	1.17
24 × 1.5	7	0.52	0.7	2.96	1.7	24.7	1020	1.02
24 × 2.5	7	0.68	0.7	3.44	1.8	27.9	832	0.83
24 × 4	7	0.85	0.7	3.95	1.9	31.2	697	0.70
27 × 1	7	0.43	0.7	2.69	1.6	23.4	1170	1.17
27 × 1.5	7	0.52	0.7	2.96	1.7	25.4	1020	1.02
27 × 2.5	7	0.68	0.7	3.44	1.8	28.5	832	0.83
27 × 4	7	0.85	0.7	3.95	1.9	31.9	697	0.70
30 × 1	7	0.43	0.7	2.69	1.7	24.1	1170	1.17
30 × 1.5	7	0.52	0.7	2.96	1.7	26.2	1020	1.02
30 × 2.5	7	0.68	0.7	3.44	1.8	29.5	832	0.83
37 × 1	7	0.43	0.7	2.69	1.7	26.0	1170	1.17
37 × 1.5	7	0.52	0.7	2.96	1.8	28.1	1020	1.02
37 × 2.5	7	0.68	0.7	3.44	1.9	29.6	832	0.83